

## Product Data Sheet

### SORB<sup>®</sup>XT Quick'n Easy ESD

### 400x400

Article	SORB <sup>®</sup> XT Quick'n Easy ESD 400x400
Article No.	100762
Dimensions (mm)	400x400x120
Weight	0,6KG
Filling quantity	19,00L



## Product Information:

### Recommended use

- the SORB<sup>®</sup>XT Quick'n Easy ESD is intended for protection of persons and objects in case of undesired leakage of liquids of liquids such as water, petroleum and chemical substances
- the use of special antistatic foil during production guarantees the prescribed conductivity for use in an environment with increased fire risk or explosive environment

### Application

- place below area of expected spill of contaminated material
- use as a collecting container
- suitable for indoor and outdoor use

### After application

- after use it is easy to clean with soap and water

### Properties

- made of special PES/PVC material with high conductivity
- stiffeners are welded into the side walls to reinforce the shape
- temperature range for use is from -10 °C to + 70 °C
- foldable
- low weight
- easy to use even in hard to reach places

## Technical Data

<b>Trägergewebe</b> <b>Base fabric</b> <b>(DIN EN ISO 2076)</b>	<b>100% Polyester</b>	<b>Flächengewicht</b> <b>Total weight</b> <b>(DIN EN ISO 2286-2)</b>	<b>550 g/m<sup>2</sup> / 16 oz/yd<sup>2</sup></b> <b>(-5% / +10%)</b>
<b>Beschichtungsmaterial</b> <b>Coating material</b>	<b>unlackiert, matt, geprägt</b> <b>unlackuered, matt</b> <b>embossing</b>		
<b>Höchstzugkraft Kette</b> <b>/Schuss</b> <b>Tensile strength</b> <b>warp/weft</b>	<b>DIN EN ISO 1421-1</b>		<b>≥ 2300/2200 N/5 cm</b> <b>≥263/251 lbf/inch</b>
<b>Weiterreißkraft Kette /</b> <b>Schuss</b> <b>Tear resistance warp/weft</b>	<b>DIN 53363</b>		<b>≥ 250/200 N</b> <b>≥ 56/45 lbf</b>
<b>Haftfestigkeit</b> <b>(nach Klebverfahren)</b> <b>Coating adhesion</b>	<b>DIN EN ISO 2411</b>		<b>≥ 80 N/5 cm</b> <b>≥ 9 lbf/inch</b>
<b>Kältebeständigkeit</b> <b>Cold resistance</b>	<b>DIN EN 1876-1</b>		<b>-30 ° C</b> <b>-22 ° F</b>
<b>Wärmebeständigkeit</b> <b>Heat resistance</b>	<b>N-Q-PA-1057</b>		<b>+70 ° C</b> <b>+158 ° F</b>
<b>Knickverhalten</b> <b>Flex resistance</b>	<b>DIN 53359 A</b>		<b>mind. 100.000</b> <b>Knickungen</b> <b>at least 100.000 bends</b>
<b>Antistatik</b> <b>Antistatic</b>	<b>in Anlehnung DIN EN 1149-1</b>		<b>Oberflächenwiderstand</b> <b>&lt;109 □</b> <b>Surface resistance</b> <b>&lt; 109 □</b>

**SORB®XT Quick Containers are not suitable for long-term storage or for the storage of substances and chemical substances. The products are designed as a quick solution for emergency and incident situations.**